



Electric Floor Heating

MiniCable F Electric Floor Heating Cable System

Combined the highest comfort levels with maximum energy efficiency. It's a proven technology that's safe, reliable and energy efficient.



- Single point connection
- Twin-conductor cable
- Emits zero EMF(electromagnetic fields)
- Safety approved for wet locations
- Flexible installation
- Durable construction
- 25 years limited warranty

MiniCable F Specifications

Application	Indoor underfloor heating, normally used under tile
Certificates	CE
Cable construction	Twin conductor
Rated Voltage	230V
Output Power	10W/m
Cable Conductor Insulation	Fluoropolymer
Cable Outer Insulation	Fluoropolymer
Cable diameter	2mm
Cold lead	2.5m long
Warranty	25-year
Package	White box

Ordering Information

230V	Output (W)	Length(m)	Amps	ohms
Catalog Number				
MinicableF/10-115	115	11.5	0.5	460
MinicableF/10-140	140	14	0.6	377.9
MinicableF/10-170	170	17	0.7	311.2
MinicableF/10-225	225	22.5	1	235.1

📍 Wuhu jiahong New Material CO., Ltd

🌐 www.ahjiahong.com

Address: No.86 Guandoumen Road, Jiujiang Economic Development Zone, China (Anhui) Pilot Free Trade Zone Wuhu Zone TEL: 0086-553-5317448, FAX:0086-553-5317408



MiniCable F

MinicableF/10-290	290	29	1.3	182.4
MinicableF/10-350	350	35	1.5	151.1
MinicableF/10-400	400	40	1.7	132.3
MinicableF/10-480	480	48	2.1	110.2
MinicableF/10-560	560	56	2.4	94.5
MinicableF/10-640	640	64	2.8	82.7
MinicableF/10-700	700	70	3	75.6
MinicableF/10-760	760	76	3.3	69.6
MinicableF/10-820	820	82	3.6	64.5
MinicableF/10-920	920	92	4	57.5
MinicableF/10-1040	1040	104	4.5	50.9
MinicableF/10-1140	1140	114	5	46.4
MinicableF/10-1250	1250	125	5.4	42.3
MinicableF/10-1450	1450	145	6.3	36.5
MinicableF/10-1600	1600	160	6.9	33.1
MinicableF/10-1800	1800	180	7.8	29.4

 Wuhu jiahong New Material CO., Ltd

 www.ahjiahong.com

Address: No.86 Guandoumen Road, Jiujiang Economic Development Zone, China (Anhui) Pilot Free Trade Zone Wuhu Zone TEL: 0086-553-5317448, FAX:0086-553-5317408